

Medium gloss floor emulsion

Description

Floor emulsion that provides a silk-like shine for most types of smooth and water resistant hard floors. Its technology provides superior adhesion on most floors and provides superior traffic resistance against scuffs and dirt. It ensures reduced maintenance costs to improve productivity.

Key properties

- Provides a silk-like, protective layer
- Hard, durable and wear resistant protection
- Excellent adhesion to most floor types
- Slip resistant according to international standards (ASTM D-2047)
- Easy to repair

Benefits

- Enhances the natural appearance of the floor by providing a silk like gloss finish
- Superior resistance to scuff marks and dirt, even under heavy traffic
- Suitable for most types of floors such as vinyl, synthetic, linoleum, stone, sealed wood and cork floors. Spreads evenly for perfect levelling
- Guaranteed slip fall prevention and safety for your employees and customers
- Responds to most common maintenance methods
- Suitable for traditional applications with a flat mop, mop and bucket or polish applicators

Use Instructions

1. Treat only stripped and thoroughly rinsed and completely dry floors. Treat porous and damaged floors with Diversey's floor sealer prior to application.
2. Sparingly pour the product onto the floor and evenly spread it while still wet in overlapping lanes of 1-1.5m.
3. Allow to dry completely.
4. Buff with single disc machine before applying subsequent coats.
5. Apply a second coat and where necessary additional coats in the same manner, buffing after every coat including the last one.

Top stripping and recoating:

1. Use a Diversey floor top stripper to remove one coat of polish and pick up soiled solution with a scrubber drier or wet vacuum cleaner.
2. Allow to dry completely before applying additional coats

Dosage*

Ready to use, no dilution required.


Product consumption: min 20 ml/m² & coat - max. 30 ml/m² & coat

** The product doesn't contain intentionally added fluorinated levelling agents (PFAS).

*This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.



NO INTENTIONALLY
ADDED PFAS**



© A.I.S.E



TASKI® Jontec Satin & Care

Technical data

Appearance:	Milky, light brown to white liquid
pH value (neat):	≈ 8.8
pH value (in use):	≈ 8.8
Relative density (20°C):	≈ 1.03

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature. Only for professional users / specialists.

Product compatibility

Treat only deep cleaned, thoroughly rinsed and completely dry floors. Do not dilute or mix with other substances. Do not use on structured plastic (cushioned vinyl) and unsealed wood or cork. Seek advice for use on profiled/studded rubber floors. Do not use outdoors or in wet zones.

Approvals

Slip resistance 0.7 minimum (ASTMD D 2047).

Available pack sizes

TASKI Jontec Satin & Care is available in 2x5L.

www.diversey.com

© 2024 Diversey, Inc. All Rights Reserved. 14/09/2024 en (K02347)